GLANCETRON



Glancetron 1200

Magnetic Card Reader for Advanced Applications

- Cost-effective, compact magnetic card reader
- Reads all three standard tracks
- suitable for credit cards, EC cards, customer cards and more
- Easy-to-use USB port
- Available in black

Specifications

General	
Decoding Capability	ISO-7811 single track: track 1, track 2, track 3 / ISO-7811 dual track: tracks 1&2, tracks 2&3 / ISO-7811 triple track: tracks 1&2&3
Magnetic Head Life	300,000 passes
Status Indicator	Audible beep for each stripe and successful read
Card Reading Speed	Bi-directional, 7.5 - 125 cm/sec
System Compatibilities	The standard RS232C and keyboard interface operates with IBM AT, PS/2 and Compatibles. The USB interface operates with USB port on IBM AT or compatibles.
Power	Model MCR K: from KB port, 5V / Model MCR R: from external power supply, 5V / Model MCR U: from USB port, 5V
Dimensions	115 mm X 46 mm X 34 mm (W x H x D)
Weight	100 g
Colour	White & dark grey
Operating Temperature	0° C - 45° C (32° F - 113 °F)
Operating Humidity	0% - 80% RH non-condensing
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Storage Humidity	10% - 90% RH non-condensing
Certification	FCC, CE, RoHS, Class A



Your Dealer

Subject to change without notice.